

**KT 50****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Cutting tools in mechanical ratchet version. Suitable for non-pinch cutting of copper and aluminium conductors. Easy operation thanks to optimum leverage and a cleverly engineered cam mechanism.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Cutting tools              |
| Order No.  | <a href="#">2993500000</a> |
| Type       | KT 50                      |
| GTIN (EAN) | 4099986874329              |
| Qty.       | 1 pc(s).                   |

## KT 50

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |             |
|------------|---------|-----------------|-------------|
| Depth      | 40 mm   | Depth (inches)  | 1.575 inch  |
| Height     | 110 mm  | Height (inches) | 4.331 inch  |
| Width      | 345 mm  | Width (inches)  | 13.583 inch |
| Net weight | 1,370 g |                 |             |

## Cutting tools

|                                        |           |                                                  |                     |
|----------------------------------------|-----------|--------------------------------------------------|---------------------|
| Aluminium sector cable                 | 4 x 70 SE | Copper cable - flexible, max.                    | 400 mm <sup>2</sup> |
| Copper cable - flexible, max. (kcmil)  | 800 kcmil | Copper cable - stranded, max.                    | 400 mm <sup>2</sup> |
| Copper cable - stranded, max. (kcmil)  | 800 kcmil | Copper cable, max. diameter                      | 52 mm               |
| Copper sector cable                    | 4 x 70 SM | Stranded aluminium cable, max (mm <sup>2</sup> ) | 400 mm <sup>2</sup> |
| Stranded aluminium cable, max. (kcmil) | 800 kcmil | Stranded aluminium cable, max. diameter          | 52 mm               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000142    | ETIM 7.0    | EC000142    |
| ETIM 8.0    | EC000142    | ETIM 9.0    | EC000142    |
| ETIM 10.0   | EC000142    | ECLASS 9.0  | 21-04-47-01 |
| ECLASS 9.1  | 21-04-90-11 | ECLASS 10.0 | 21-04-47-01 |
| ECLASS 11.0 | 21-04-47-01 | ECLASS 12.0 | 21-04-47-01 |
| ECLASS 13.0 | 21-04-47-01 | ECLASS 14.0 | 21-04-47-01 |
| ECLASS 15.0 | 21-04-47-01 |             |             |

## Environmental Product Compliance

|                        |                                      |
|------------------------|--------------------------------------|
| RoHS Compliance Status | Not affected                         |
| REACH SVHC             | Lead 7439-92-1                       |
| SCIP                   | cf06c250-ed1e-4a45-9c1b-c5c8cbf13bf0 |

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|